

7-Channel WRSAME Weatheradio w/Alert  
(120-0250) Specifications

Faxback Doc. # 51412

Frequency Coverage (MHz): Channel 1: ..... 162.400  
Channel 2: ..... 162.425  
Channel 3: ..... 162.450  
Channel 4: ..... 162.475  
Channel 5: ..... 162.500  
Channel 6: ..... 162.525  
Channel 7: ..... 162.550

Receiving Sensitivity (at 12 dB SINAD): ..... 0.3 uV

FIPS Code Sensitivity @ +/- 3 kHz Deviation/90% Success Rate: ..... 0.3 uV

Signal to Noise Ratio: ..... 40 dB

Dual Tone Detection Range: ..... 1.2 to 2.4 kHz

Channel Selectivity: ..... +/- 25 kHz, 60 dB

Power Output (Maximum): ..... 250 mW

Power Supply: ..... 120 Volts, 60 Hz, 5 Watts AC

Battery Back-up: ..... One 9 Volt Battery (Cat. No. 23-553)

Antenna: ..... Telescoping Rod Antenna

Dimensions (HWD): .... 7-1/20 x 5-1/2 x 1-17/20 Inches (179 x 140 x 47 mm)

Weight: ..... 20.28 oz (575 g)

Specifications are typical; individual units might vary. Specifications are subject to change and improvement without notice.

(EB 2/15/99)