



东莞篁村新能源电子厂 Amperex Technology Limited DongGuan Plant

BaiMa Industrial Park, HuangCun, DongGuan, GuangDong, PRC 523080
广东省东莞市篁村白马管理区仲胜科技园 523080
Tel: 86-769-240-5338 Fax: 86-769-240-6593

ATL LITHIUM ION POLYMER BATTERY SAFETY DATA SHEET

PRODUCT NAME: Amperex Technology Limited

Type No.: **Volts:**

TRADE NAME: Lithium Ion Polymer Battery

Approximate Weight:

CHEMICAL SYSTEM: Lithium Ion

Designed for Recharge: Yes

SECTION I - MANUFACTURER INFORMATION

Manufactured for:

Amperex Technology Limited

Telephone Number for Information

Bai Ma Industrial Park, Huang Cun, Dong Guang

Tel: 86-769-240-5338

Guang Dong, China

Fax:86-769-240-6593

Zip Code:523080

Date Prepared: **November 18, 2001**

SECTION II - HAZARDOUS INGREDIENTS

IMPORTANT NOTE: The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful.

MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Graphite (CAS# 7782-42-5)	5 mg/m3 TWA (respirable fraction) 15 mg/m3 TWA (total dust)	2 mg/m3 TWA (respirable fraction)	7-25
Lithium Cobalt Oxide (CAS# 12190-79-3)	0.1 mg/m3 TWA (as Co)	0.02 mg/m3 TWA (as Co)	15-40
Hexafluoropropylene-vinylidene fluoride Copolymer (CAS#9011-17-0)	None established	None established	3-15

HK Headquarters (香港总部)
3503, Wharf Cable TV Tower, 9 Hoi Shing Road, Tsuen Wan, N.T., HongKong
香港新界荃湾海盛路9号有线电视大楼35楼3号单位
Tel: 852-2498-0908 Fax: 852-2498-1101



东莞篁村新能源电子厂

Amperex Technology Limited DongGuan Plant

BaiMa Industrial Park, HuangCun, DongGuan, GuangDong, PRC 523080
广东省东莞市篁村白马管理区仲胜科技园 523080
Tel: 86-769-240-5338 Fax: 86-769-240-6593

Lithium Hexafluorophosphate (CAS# 21324-40-3)	None established	None established	0-5
MATERIAL OR INGREDIENT	PEL (OSHA)	TLV (ACGIH)	%/wt.
Acetylene Black (CAS# 1333-86-4)	3.5 mg/m3 TWA (as carbon black)	3.5 mg/m3 TWA (as carbon black)	0-2
Diethyl Carbonate (CAS# 105-58-8)	None established	None established	0-15
Dimethyl Carbonate (CAS# 616-38-6)	None established	None established	0-15
Ethyl Methyl Carbonate (CAS# 623-53-0)	None established	None established	0-15
Propylene Carbonate (CAS# 108-32-7)	None established	None established	0-15
Ethylene Carbonate (CAS# 96-49-1)	None established	None established	0-15

SECTION III - FIRE AND EXPLOSION HAZARD DATA

If fire or explosion occurs when batteries are on charge, shut off power to charger

In case of fire where lithium ion batteries are present, flood the area with water. If any batteries are burning, water may not extinguish them, but will cool the adjacent batteries and control the spread of fire. CO₂, dry chemical, and foam extinguishers are preferred for small fires, but also may not extinguish burning lithium ion batteries. Burning batteries will burn themselves out. Virtually all fires involving lithium ion batteries can be controlled with water. When water is used, however, hydrogen gas may be evolved which can form an explosive mixture with air. LITH-X (powdered graphite) or copper powder fire extinguishers, sand, dry ground dolomite or soda ash may also be used. These materials act as smothering agents.



东莞篁村新能源电子厂

Amperex Technology Limited DongGuan Plant

BaiMa Industrial Park, HuangCun, DongGuan, GuangDong, PRC 523080

广东省东莞市篁村白马管理区仲胜科技园 523080

Tel: 86-769-240-5338 Fax: 86-769-240-6593

Fire fighters should wear self-contained breathing apparatus. Burning lithium ion batteries can produce toxic fumes including HF, oxides of carbon, aluminum, lithium, copper, and cobalt. Volatile phosphorus pentafluoride may form at a temperature above 230° Fahrenheit.

SECTION IV - HEALTH HAZARD DATA

Under normal conditions of use, the battery is hermetically sealed.

Ingestion: Swallowing a battery can be harmful.

Contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract.

If battery or open battery is ingested, do not induce vomiting or give food or drink. Seek medical attention immediately.

Inhalation: Contents of an open battery can cause respiratory irritation. Inhalation of vapors may cause irritation of the upper respiratory tract and lungs. Provide fresh air and seek medical attention.

Skin Absorption: Ethylene carbonate, diethyl carbonate and dimethyl carbonate may be absorbed through the skin causing localized inflammation.

Skin Contact: Contents of an open battery can cause skin irritation and/or chemical burns. Remove contaminated clothing and wash skin with soap and water. If a chemical burn occurs or if irritation persists, seek medical attention.

Eye Contact: Contents of an open battery can cause severe irritation and chemical burns. Immediately flush eyes thoroughly with water for at least 15 minutes, lifting upper and lower lids, until no evidence of the chemical remains. Seek medical attention.

Note: Acetylene black and cobalt compounds are listed as possible carcinogens by the International Agency for Research on Cancer (IARC).

SECTION V - PRECAUTIONS FOR SAFE HANDLING AND USE



东莞篁村新能源电子厂

Amperex Technology Limited DongGuan Plant

BaiMa Industrial Park, HuangCun, DongGuan, GuangDong, PRC 523080
广东省东莞市篁村白马管理区仲胜科技园 523080
Tel: 86-769-240-5338 Fax: 86-769-240-6593

Storage: The lithium ion battery should be between 25% and 75% of full charge when stored for a long period of time. Store in a cool, dry, well ventilated area. Elevated temperatures can result in loss of battery performance, leakage, or rust. Do not expose the battery to open flames.

Handling: Do not expose the battery to excessive physical shock or vibration. Short-circuiting should be avoided, however, accidental short-circuiting for a few seconds will not seriously affect the battery. Prolonged short circuits will cause the battery to rapidly lose energy, could generate enough heat to burn skin. Sources of short circuits include jumbled batteries in bulk containers, coins, metal jewelry, metal covered tables, or metal belts used for assembly of batteries in devices. To minimize risk of short-circuiting, the protective case supplied with the battery should be used to cover the terminals when transporting or storing the battery. Do not disassemble or deform the battery. Should an individual cell within a battery become ruptured, do not allow contact with water.

If soldering or welding to the battery is required, consult your company representative for proper precautions to prevent damage to the integrity of the battery.

Charging: This battery is made to be charged many times. Use an Energizer approved battery charger. Never use a modified or damaged battery charger. A backup charge termination based on time is recommended to prevent overcharging. The charging temperature should be between 0° C and 50° C (32° F and 120° F). The battery pack will normally warm during charging.

Charging Voltages and Currents: Charging voltages are prevented from exceeding the specified limits by an internal battery protection circuit. Never use a battery that shows signs of a damaged protection circuit or broken case. (Such damage to the protection circuit may be indicated by voltages at the battery terminals outside of their specified ranges.) Adhere to all specified charging and discharging voltages and currents. Do not use battery if its voltage drops below the specified minimum voltage.

Labeling: If the ATL label or package warnings are not visible, it is important to provide a package and/or device label stating:

**WARNING:CHARGE ONLY WITH SPECIFIED CHARGERS ACCORDING TO
DEVICE MANUFACTURER'S INSTRUCTIONS. DO NOT OPEN BATTERY,
DISPOSE OF IN FIRE, OR SHORT CIRCUIT - MAY IGNITE, EXPLODE, LEAK,
OR GET HOT CAUSING PERSONAL INJURY.**

Disposal: Dispose in accordance with all applicable federal, state and local regulations.



东莞篁村新能源电子厂

Amperex Technology Limited DongGuan Plant

BaiMa Industrial Park, HuangCun, DongGuan, GuangDong, PRC 523080
广东省东莞市篁村白马管理区仲胜科技园 523080
Tel: 86-769-240-5338 Fax: 86-769-240-6593

SECTION VI - SPECIAL PROTECTION INFORMATION

Ventilation Requirements: Not necessary under normal conditions.

Respiratory Protection: Not necessary under normal conditions.

Eye Protection: Not necessary under normal conditions. Wear safety glasses with side shields if handling an open or leaking battery.

Gloves: Not necessary under normal conditions. Use neoprene or natural rubber gloves if handling an open or leaking battery.

Open Battery Storage: Battery should not be opened. Should a cell become disassembled, the electrode should be stored in a fireproof cabinet, away from combustibles.