

MODELS

Compaq FS7550 Color CRT Monitor
 Part Number: 261608-001
 UPC: 720591213275

SPECIFICATIONS

Tube Type	Color, Flat-faced Shadow Mask, multi-frequency			
Picture Tube Size (diagonal)	17-inch (43.18 cm)			
Viewable Image Area (diagonal)	16-inch (40.64 cm)			
Trio Dot Pitch	0.25 to 0.28 mm			
Horizontal Dot Pitch	0.22 to 0.24 mm			
Horizontal Frequency (kHz)	30 to 86 kHz			
Vertical Frequency (Hz)	50 to 140 Hz			
Maximum Pre-set Resolution	1600 x 1200 @ 65 Hz			
Preferred Flicker Free Resolution	1024 x 768 @ 85 Hz			
Preset Graphic Modes	1600 x 1200	1280 x 1024	1024 x 768	800 x 600
Note: All modes are non-interlaced unless specified otherwise.	@ 65 Hz	@ 75 Hz	@ 85 Hz and 75 Hz	@ 85 Hz and 75 Hz
	720 x 400	640 x 480		
	@ 70 Hz	@ 85 Hz, 75 Hz and 60 Hz		
User Modes	Yes, 8 modes			
Anti-Glare/Anti-Static	Yes			
AssetControl	Yes			
Plug and Play	Yes			
Icon Based On-Screen Display Controls	Yes			
User Controls	Brightness, Contrast	Yes		
	Size and Positioning	Yes		
	Pincushion (barrel)	Yes		
	Trapezoid	Yes		
	Tilt (rotation)	Yes		
	Selectable Color temperature	Yes		
	Parallelogram	Yes		
	Pincushion Balance	Yes		
	Exit	Yes		
	Degauss	Yes		
	Factory Reset/Recall	Yes		
	Current Display Mode	Yes		

SPECIFICATIONS *(continued)*

Approvals/Certifications	UL/CSA/CUL Approval	Yes
	ISO9241-3, -7, -8 VOT Guidelines Approval	Yes
	MPR-II Compliant	Yes
	TCO '99	Yes, selected models
	FCC Approval	Yes
	Microsoft WHQL Certified	Yes
	CE	Yes
	Energy Star Compliant	Yes
Maximum Pixel Clock Speed	180 MHz	
Power Supply	Universal; 100 to 240 V, 50 ± 3Hz and 60 ± 3Hz	
Maximum Power Rating	100 Watts	
Low Power Sleep Mode	< 5 watts	
Signal Cable	15-pin miniature D-sub, attached, 5.9 feet (1.8 meter)	
Dimensions (H x W x D)	(Unpacked)	17.0 x 16.1 x 17.4 in (43.2 x 40.9 x 44.2 cm)
	(Packaged)	22.8 x 22.4 x 23.9 in (58.0 x 57.0 x 60.6 cm)
Weight	(Unpacked)	41.8 lb (19 kg)
	(Packaged)	50.6 lb (23.0 kg)
Operating Temperature (non-condensing)	50° to 85° F (10° to 35° C)	
Operating Humidity (non-condensing)	20% to 80%	
Express Service	Compaq Express Service offers 48-hour advanced exchange replacement with a new or refurbished Compaq monitor	
Warranty	One-year parts and labor, limited warranty. Certain restrictions and exclusions apply. For details, contact Compaq Customer Support at 1-800-OKCOMPAQ.	

JBL PLATINUM SERIES SPEAKER SPECIFICATIONS

On/Off/Volume Control and LED	Yes, front panel of right speaker	
Line Input Jack	Yes, (Digital Audio Port Input)	
Sound Output	3 watt RMS per channel @ 10% Total Harmonic Distortion (THD)	
Frequency Response	100 Hz to 20 kHz	
Sound Pressure Level	86 dB (1 watt/1 meter) averaged at 300, 400, 500, 600 Hz	
Nominal Impedance (3-inch Driver)	4 ohms	
Speaker Weight	Right	1.26 lb (572 g)
	Left	1.12 lb (506 g)
Speaker Dimensions (H x W x D)	9 x 3.3 x 4 in (22.86 x 8.38 x 10.16 cm) per speaker	
Power Supply (USA)	Input	120V, 60Hz, 25W
	Output	12V (DC), 1 amp
Speaker Cable Lengths	Audio Signal Cable	6.23 feet (1.9 meter)
	Right Speaker to Left Speaker	5.9 feet (1.8 meter)
	Power Adapter	6 feet (1.83 meter)
Cabinet and Grill Color	Black	

Compaq, registered United States Patent and Trademark Office. Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.

©2001 Compaq Computer Corporation.