

MODELS

Flat Panel FP5017 Color Monitor
Two-Tone (Carbon/Silver)
Part Number: 263873-001
UPC: 613326269336

SPECIFICATIONS

Panel Type	15" Active Matrix TFT (thin film transistor)		
LCD Active Area (Diagonal)	15 in/38.1 cm		
Screen Opening (W x H)	12 x 9 in/31 x 23 cm		
Signal Input	15 pin D-sub (Analog VGA)		
Contrast Ratio (typical)	350:1		
Response Rate	25 ms (typical)		
Brightness (typical)	250 nits		
Viewing Angle (H x V)	120 x 90 (10:1 contrast ratio)		
Pixel Pitch	0.3 mm		
Horizontal Frequency (kHz)	30 to 61 kHz		
Vertical Frequency (Hz)	56 to 75 Hz		
Graphics Controller	Sage or Philips		
Factory Present Modes	12		
Preset Graphic Modes	1024 x 768	800 x 600	640 x 480
NOTE: All modes are non-interlaced unless specified otherwise.	@ 60 Hz, 70 Hz and 75 Hz	@ 60 Hz, 72 Hz and 75 Hz	@ 60 Hz, 72 Hz and 75 Hz
Text Mode	720 x 400 @ 70 Hz		
Mac Compatible Modes*	832 x 624 @ 75 Hz		
VGA Mode	832 x 624 @ 75 Hz		
NOTE: * = Adapter required.			
User-Programmable Modes	8		
Anti-Glare	Yes		
Anti-Static	Yes		
AssetControl	Yes		
Plug and Play	Yes		

SPECIFICATIONS *(continued)*

Icon Based On-Screen Display Controls	Yes
User Controls	
Brightness, Contrast	Yes
Positioning	Yes
Color temperature (6500k, 9300k, Custom)	Yes
Individual color control	Yes
Serial Number Display	No
Full Screen 640 x 480, 800 x 600 Resolutions	Yes
Clock	Yes
Clock Phase	Yes
Monitor Management	Power On Recall (on/off), Power Saver (on/off), Mode Display (on/off), Sleep Timer
Factory Reset	Yes
Agency Approvals/Certifications	
TCO 99 (Low Emissions)	Select Models
ISO 13406-2 VDT Guidelines Approval	Yes
ISO 9241 – 3,7,8	Yes
MPR-II Compliant	Yes
CISPR Requirements	Yes
VCCI Approvals	Yes
MIC (New Zealand) Requirements	Yes
Canadian Requirements	Yes
Australian SMA Approval	Yes
"GS" Mark, TUV Approvals	Yes
CE Marking	Yes
FCC Approval	Yes
Energy Star Compliant	Yes
Windows Certification	Windows 98, Windows 2000, and Windows XP
Language Selection	
English	Yes
Spanish	Yes
French	Yes
German	Yes
Dutch	Yes
Italian	Yes
Pixel Clock Speed	78.75MHz
Input Impedance	75 ohms \pm 10%
Horizontal Frequency	31.47 to 60 kHz
Vertical Frequency	58 to 75 Hz

SPECIFICATIONS *(continued)*

Power Supply ALS	Universal/Auto-Sensing, 90 to 264 VAC, 47.5 to 63 Hz	
Maximum Power Rating	< 45W	
Audio (2 Speakers, Volume Control, Headphone Jack)	2W per Channel Frequency Response 250 Hz to 20 KHz Total harmonic distortion 3% at 1.5W (100 Hz to 13 kHz)	
Suspend/Sleep	<5W	
Synch Input	TTL separate synch	
Detachable Base	Yes	
Tilt	Yes (35° up and 5° down)	
Swivel	No	
Kensington Lock-ready	Yes	
Accessories Included	VGA cable, Universal Power adaptor, AC Power Cord, Audio Cable (select models)	
Protective Panel	No	
Touchscreen Option	No	
VESA Mounting	75 mm and 100 mm Hole Patterns	
Dimensions	Unpacked (W x H x D)	13.7 x 15.1 x 5.8 in/34.9 x 38.6 x 14.7 cm
	Packed (W x H x D)	17.4 x 19.5 x 7.6 in/44.2 x 49.5 x 19.3 cm
Weight	Unpacked	8.8 lb/4.0 kg
	Packed	11.44 lb/5.2 kg
Temperature	Operating	41° to 95° F/5° to 35° C
	Non-operating	-4° to 140° F/-20° to 60° C
Humidity	Operating	20% to 80%
	Non-operating	5% to 95%
Warranty	One-year parts and labor, limited warranty. Certain restrictions and exclusions apply. For details, contact Compaq Customer Support at 1-800-OKCOMPAQ.	